

Filter unit F-701-W1 is the liquid phase filter unit with an exchangeable cartridge suitable for the 11-kg propane-butane cylinders used in the fork lift trucks.

1. Exchange the filter cartridge or the filter unit after maximum 100 hours of engine work for the fork lift trucks or after 10 000 km for the motor vehicles.*
2. Install the filter according to the flow direction shown on the body (a pointer).
3. Avoid any mechanical damages while installing the filter unit and during its usage.
4. Do not use with pressure over 3000 kPa.
5. Work temperature range from -20°C to 120°C.
6. Check the installation tightness after installing the filter.
7. Use only original elements (KN-701) while replacing or cleaning.
8. Exchange all o-rings while exchanging the filter cartridge.
9. Remove the filter from the installation before exchanging the filter cartridge.
10. Set the filter unit in a vice or any other proper handle before disengaging.
11. Disconnect the bottom from the body with a torque spanner with 20 Nm moment.
12. Install not to damage any flexible hoses.
13. Hold all installation, exchanging the filter cartridge or the filter unit and any repairs in the certified services.
14. Use the filter only for what it was intended.
15. Utilize the filter in accordance with the law.



* Liveliness of the filter unit depends on the fuel quality. It is recommended to refuel in the certified petrol stations.

APPROVAL:

67R-010531

class 1